

Jiang et al.

S/N: 10/707,405

In the Claims

1. (Currently Amended) A CT detector comprising:
a scintillator array having a plurality of
scintillators; and
a reflector interstitially disposed between at least
two adjacent scintillators, the reflector including a light
absorption element disposed between a pair of reflective
elements; and
a reflective layer coated to a face of the
scintillator array.

2. (Canceled)

3. (Original) The CT detector of claim 1 wherein the
light absorption element is configured to reduce optical cross-
talk between the at least two adjacent scintillators.

4. (Original) The CT detector of claim 3 wherein the
light absorption element is configured to substantially eliminate
optical cross-talk between the at least two adjacent
scintillators.

5. (Canceled)

6. (Canceled)

7. (Canceled)

8. (Canceled)

9. (Canceled)

Jiang et al.

S/N: 10/707,405

10. (Canceled)

11. (Canceled)

12. (Canceled)

13. (Original) The CT detector of claim 1 incorporated into a CT imaging system.

14. (Original) The CT detector of claim 13 wherein the CT imaging system is configured to acquire radiographic data of a medical patient.

15. (Currently Amended) A CT system comprising:

a rotatable gantry having a bore centrally disposed therein;

a table movable fore and aft through the bore and configured to position a subject for CT data acquisition;

a high frequency electromagnetic energy projection source positioned within the rotatable gantry and configured to project high frequency electromagnetic energy toward the subject; and

a detector array disposed within the rotatable gantry and configured to detect high frequency electromagnetic energy projected by the projection source and impinged by the subject, the detector array including:

a scintillator array configured to illuminate upon reception of radiographic energy;

a reflector assembly disposed between adjacent scintillators of the scintillator array; and

wherein each reflector assembly includes a layer sandwiched between at least a pair of reflective layers; and

Jiang et al.

S/N: 10/707,405

wherein the composite layer includes a high-Z metal and a low-viscosity polymer.

16. (Canceled)

17. (Currently Amended) The CT system of claim ~~16~~15 wherein the high Z-metal includes one of tungsten and tantalum.

18. (Currently Amended) The CT system of claim ~~16~~15 wherein the low-viscosity polymer has a non-translucent color.

19. (Original) The CT system of claim 15 wherein the at least a pair of reflective layers includes TiO_2 .

20. (Original) The CT system of claim 15 wherein each reflective layer has a lateral thickness of approximately 15-90 μm and the composite layer has a lateral thickness of approximately 50-100 μm .

21. (Original) The CT system of claim 15 wherein the reflector assembly is cast between adjacent scintillators.

22. (Currently Amended) A method of CT detector manufacturing comprising the steps of:

providing a scintillator array of a plurality of scintillators, wherein the step of providing a scintillator array includes the step of forming a substrate of scintillation material;

Jiang et al.

S/N: 10/707,405

disposing a reflective layer between adjacent scintillators; and

disposing a composite layer in the reflective layer.

23. (Canceled)

24. (Currently Amended) The method of claim ~~23~~ 22 further comprising the step of pixelating the substrate.

25. (Currently Amended) The method of claim 24 wherein the step of pixelating includes at least one of chemically and mechanically forming gaps in the substrate to define ~~a~~ the plurality of scintillators.

26. (Original) The method of claim 25 wherein mechanically forming gaps includes dicing the substrate.

27. (Original) The method of claim 25 further comprising the step of depositing reflective material into at least the gaps.

28. (Original) The method of claim 27 wherein the step of depositing includes the step of casting.

29. (Original) The method of claim 27 wherein the step of disposing a composite layer in the reflective layer includes the step of creating channels in the reflective material.

Jiang et al.

S/N: 10/707,405

30. (Original) The method of claim 29 wherein the step of creating includes at least one of laser cutting, wire cutting, and etching.

31. (Original) The method of claim 29 further comprising the step of depositing composite material into the channels.

32. (Original) The method of claim 31 wherein the composite material includes a metal and a polymer.

33. (Original) The method of claim 31 wherein the step of depositing composite material into the channels includes casting.

34. (New) A CT detector comprising:

a scintillator array having a plurality of scintillators; and

a reflector interstitially disposed between at least two adjacent scintillators, the reflector including a light absorption element disposed between a pair of reflective elements, wherein the light absorption element is configured to absorb x-rays.

35. (New) The CT detector of claim 34 wherein the light absorption element is further configured to absorb approximately 50% of the x-ray photons across a gap between the at least two adjacent scintillators.

36. (New) A CT detector comprising:

a scintillator array having a plurality of scintillators; and

Jiang et al.

S/N: 10/707,405

a reflector interstitially disposed between at least two adjacent scintillators, the reflector including a light absorption element disposed between a pair of reflective elements, wherein the light absorption element is configured to reduce x-ray punch through.

37. (New) A CT detector comprising:

a scintillator array having a plurality of scintillators; and

a reflector interstitially disposed between at least two adjacent scintillators, the reflector including a light absorption element disposed between a pair of reflective elements, wherein the light absorption element includes a high atomic number metal composite.

38. (New) The CT detector of claim 37 wherein the metal composite includes a cured metal powder and low viscosity polymer combination.

39. (New) The CT detector of claim 38 wherein the polymer includes polyurethane.

40. (New) The CT detector of claim 37 wherein the metal composite includes at least one of tungsten, tantalum, and a metal powder with density greater than 16g/cm^3 .

41. (New) A CT detector comprising:

a scintillator array having a plurality of scintillators; and

a reflector interstitially disposed between at least two adjacent scintillators, the reflector including a light absorption element disposed between a pair of reflective elements, wherein the pair of reflective elements include TiO_2 .

Jiang et al.

S/N: 10/707,405

42. (New) A CT system comprising:

a rotatable gantry having a bore centrally disposed therein;

a table movable fore and aft through the bore and configured to position a subject for CT data acquisition;

a high frequency electromagnetic energy projection source positioned within the rotatable gantry and configured to project high frequency electromagnetic energy toward the subject; and

a detector array disposed within the rotatable gantry and configured to detect high frequency electromagnetic energy projected by the projection source and impinged by the subject, the detector array including:

a scintillator array configured to illuminate upon reception of radiographic energy;

a reflector assembly disposed between adjacent scintillators of the scintillator array; and

wherein each reflector assembly includes a layer sandwiched between at least a pair of reflective layers; and

wherein the at least a pair of reflective layers includes TiO_2 .

43. (New) A CT system comprising:

a rotatable gantry having a bore centrally disposed therein;

a table movable fore and aft through the bore and configured to position a subject for CT data acquisition;

a high frequency electromagnetic energy projection source positioned within the rotatable gantry and configured to project high frequency electromagnetic energy toward the subject; and

Jiang et al.

S/N: 10/707,405

a detector array disposed within the rotatable gantry and configured to detect high frequency electromagnetic energy projected by the projection source and impinged by the subject, the detector array including:

a scintillator array configured to illuminate upon reception of radiographic energy;

a reflector assembly disposed between adjacent scintillators of the scintillator array; and

wherein each reflector assembly includes a layer sandwiched between at least a pair of reflective layers; and

wherein each reflective layer has a lateral thickness of approximately 15-90 μm and the composite layer has a lateral thickness of approximately 50-100 μm .

44. (New) A CT system comprising:

a rotatable gantry having a bore centrally disposed therein;

a table movable fore and aft through the bore and configured to position a subject for CT data acquisition;

a high frequency electromagnetic energy projection source positioned within the rotatable gantry and configured to project high frequency electromagnetic energy toward the subject; and

a detector array disposed within the rotatable gantry and configured to detect high frequency electromagnetic energy projected by the projection source and impinged by the subject, the detector array including:

a scintillator array configured to illuminate upon reception of radiographic energy;

a reflector assembly disposed between adjacent scintillators of the scintillator array; and

Jiang et al.

S/N: 10/707,405

wherein each reflector assembly includes a layer sandwiched between at least a pair of reflective layers; and

wherein the reflector assembly is cast between adjacent scintillators.